


Proximity switch SDBT-MSB-1L-ZU-K-2-LE

Part number: 8150173

FESTO



[PDF](#) [General operating condition](#)

Data sheet

Feature	Value
Design	For T-slot
Conforms to standard	EN 60947-5-2
Symbol	00991144
Approval	RCM trademark
CE mark (see declaration of conformity)	To EU EMC Directive In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
KC mark	KC-EMV
Special characteristics	Oil resistant
Note on materials	RoHS-compliant Free of halogen Free of copper
Measured variable	Position
Measuring principle	Magneto-resistive
Ambient temperature	-20 °C ... 70 °C
Repetition accuracy	0.2 mm
Switching output	Non-contacting, 2-wire
Switching element function	N/O contact
Switch-on time	≤2.5 ms
Switch-off time	≤2.5 ms
Max. switching frequency	480 Hz
Max. output current	50 mA
Max. switching capacity DC	1.4 W
Voltage drop	≤2.8 V
Short circuit current rating	no
Overload protection	No
Rated operational voltage DC	24 V
Operational voltage range DC	10 V ... 28 V
Reverse polarity protection	no
Electrical connection 1, connection type	Cable
Electrical connection 1, connector system	Open end
Electrical connection 1, number of connections/cores	2
Connection outlet orientation	In-line
Material screw-type lock	High-alloy stainless steel
Cable length	2 m
Cable characteristic	Standard Suitable for energy chains

Feature	Value
Material cable sheath	PUR
Material insulating sheath	PP
Wire ends	Cut off bluntly
Type of mounting	Screw-clamped Insertable in the slot from above
Max. tightening torque	0.3 Nm
Mounting position	optional
Product weight	24 g
Material housing	PC
Switching status indication	Yellow LED
Ambient temperature with moving cable	-20 °C ... 70 °C
Degree of protection	IP67 IP68 To IEC 60529
LABS (PWIS) conformity	VDMA24364 zone III
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Cleanroom suitability, measured according to ISO 14644-14	Element installed statically, no meaningful evaluation possible according to ISO 14644-1