

型番		Product Name		HF16XA-1F
焦点距離 [mm]		Focal length [mm] (design value)		16 (15.87)
絞り (F値)	標準プレート	Iris (Fnumber)	Standard Plate	F1.6
	プレートC		Plate "C"	F4
	プレートE		Plate "E"	F8
画角 (H × V)		Angle of view		31.4° × 23.7° (2/3")
フォーカス範囲 (レンズメカ先端より) [mm]		Working distance (from front of lens barrel) [mm]		∞ - 100
操作方法:フォーカス		Operation of focus		Fixed
操作方法:アイリス		Operation of iris		Fixed
フィルタ径 [mm]		Filter thread [mm]		M25.5 × 0.5
マウント		Mount		C-mount
質量 (約) [g]		Weight (approx.) [g]		94
適合センサーサイズ (標準)		Sensor size (std.)		2/3" (3.45μm)
適合センサーサイズ (最大)		Sensor size (max.)		1/1.2" (4.5μm)
バックフォーカス (空気換算長) [mm]		Back focal length (in air) [mm]		10,66
フランジバック [mm]		Flange back [mm]		17,526
入射瞳位置 (マウント面から) [mm]		Entrance pupil position (from Mount) [mm]		-26,80
射出瞳位置 (結像面より) [mm]		Exit pupil position (from image plane) [mm]		-258,03
前側主点 (マウント面から) [mm]		Front principal point (from Mount) [mm]		-12,33
後側主点 (マウント面から) [mm]		Rear principal point (from Mount) [mm]		1,65
主点間隔 [mm]		Distance between the principal points [mm]		13,98
TVディストーション [%]		TV distortion [%]		-0,60
外形寸法 [mm]		Dimension [mm]		φ34 × 54.0
主光線入射角度 [°]		Chief Ray Angle [°]		0,65
周辺光量比 [%] (対角端)	標準プレート	Relative illumination [%] (Image height : at diagonal)	Standard Plate	48
	プレートC		Plate "C"	90
	プレートE		Plate "E"	95
使用温度範囲		Operation Temperature Range		-10°C ~ +50°C
保存温度範囲		Storage Temperature Range		-30°C ~ +60°C

These specifications are subject to change without notice.

Feb 21