



■ Not recommended for new designs
The camera model is no longer recommended for new application development.



Specification

Sensor

| | |
|---|----------------------|
| Sensor type | CMOS Mono |
| Shutter | Global Shutter |
| Sensor characteristic | Linear |
| Readout mode | - |
| Pixel Class | 3 MP |
| Resolution | 3.17 Mpix |
| Resolution (h x v) | 2056 x 1542 Pixel |
| Aspect ratio | 4:3 |
| ADC | 12 bit |
| Color depth (camera) | 12 bit |
| Optical sensor class | 1/1.8" |
| Optical Size | 7.093 mm x 5.320 mm |
| Optical sensor diagonal | 8.87 mm 1/1.8" |
| Pixel size | 3.45 µm |
| Manufacturer | Sony |
| Sensor Model | IMX265LLR-C |
| Gain (master/RGB) | 24x/4x |
| AOI horizontal | same frame rate |
| AOI vertical | increased frame rate |
| AOI image width / step width | 256 / 8 |
| AOI image height / step width | 2 / 2 |
| AOI position grid (horizontal/vertical) | 4 / 2 |
| Binning horizontal | - |
| Binning vertical | increased frame rate |
| Binning method | Mono |
| Binning factor | 2 |
| Decimation (subsampling) horizontal | same frame rate |
| Decimation (subsampling) vertical | increased frame rate |
| Decimation (subsampling) method | M/C automatic |
| Decimation (subsampling) factor | 2 |



Subject to technical modifications (2026-01-20)

Model

| | |
|-----------------------------------|---------------------------------------|
| Pixel clock range | 10 MHz - 197 MHz |
| Frame rate freerun mode | 57 fps |
| Frame rate trigger (continuous) | 57 fps |
| Frame rate trigger (maximum) | 57 fps |
| Exposure time (minimum - maximum) | 0.024 ms - 1000 ms |
| Long exposure (maximum) | 30000 ms |
| Power consumption | 0.9 W - 1.7 W |
| Image memory | - |
| Special features | Overlap trigger Sensor source gain |

Ambient conditions

For PCB versions, refer to the separate hints in the respective documentation.


| | |
|---|---------------------------------|
| Allowed device temperature during operation | 0 °C - 55 °C / 32 °F - 131 °F |
| Allowed device temperature during storage | -20 °C - 80 °C / -4 °F - 176 °F |
| Humidity (relative, non-condensing) | 20 % - 80 % |

Connectors

| | |
|---------------------|-------------------------------------|
| Interface connector | USB Type-C |
| I/O connector | 10-pin Molex connector (IllumiMate) |
| Power supply | USB cable |

Pin assignment I/O connector

| | |
|----|---|
| 1 | Voltage output (USB Power Delivery), 5-15 V |
| 2 | Ground (GND) |
| 3 | General Purpose I/O (GPIO) 2, 3.3 V |
| 4 | General Purpose I/O (GPIO) 1, 3.3 V |
| 5 | TWI (Two Wire Interface) clock signal |
| 6 | TWI (Two Wire Interface) data signal |
| 7 | Trigger input without optocoupler 3.3 V |
| 8 | Flash output without optocoupler 3.3 V |
| 9 | Ground (GND) |
| 10 | Voltage output 3.3 V |



Design

| | |
|------------------|-----------------------------|
| Lens Mount | CS- / C-Mount |
| IP code | - |
| Dimensions H/W/L | 36.0 mm x 36.0 mm x 26.1 mm |
| Mass | 20 g |
| Housing material | - |

Features

List of on-camera image pre-processing features.

All features of the table are available via our IDS peak software for image pre-processing on the host computer (sensor model dependent).

UI-3274LE-M-GL-VU (AB02206)

| | | |
|---------------------------|--------------------------------|------|
| Image Acquisition | Freerun | ✓ |
| | Software trigger | - |
| | Hardware trigger | ✓ |
| | Trigger controlled exposure | - |
| | Denoisier | - |
| | Long exposure | ✓ |
| | Line scan | - |
| Flashing | Flashing | - |
| | PWM flashing | - |
| Image Adjustments | Auto exposure | - |
| | Auto gain | - |
| | Auto whitebalance | - |
| | Color correction | - |
| | Gamma | - |
| | LUT | - |
| | Mirror/flip | - |
| On-board Image Processing | Pixel formats | |
| | Region of interest | ✓ |
| | Decimation (FPGA) | - |
| | Decimation (Sensor) | |
| | Binning (FPGA) | - |
| Others | Chunks | - |
| | Sequencer | - |
| | Firmware update | - |
| | 1st supported firmware version | 4.82 |