

## In series


The model is in series and available for the long term.



## Specification

### Sensor

Sensor type	CMOS Color
Shutter	Global Shutter
Sensor characteristic	Linear
Readout mode	-
Pixel Class	12 MP
Resolution	12.42 Mpix
Resolution (h x v)	4128 x 3008 Pixel
Aspect ratio	4:3
ADC	12 bit
Color depth (camera)	12 bit
Optical sensor class	1/1.1"
Optical Size	11.223 mm x 8.220 mm
Optical sensor diagonal	13.91 mm 1/1.1"
Pixel size	2.74 µm
Manufacturer	Sony
Sensor Model	IMX535-AAQJ-C
Gain (master/RGB)	16x/16x
AOI horizontal	same frame rate
AOI vertical	increased frame rate
AOI image width / step width	256 / 2
AOI image height / step width	2 / 2
AOI position grid (horizontal/vertical)	2 / 2
Binning horizontal	
Binning vertical	
Binning method	M/C automatic
Binning factor	1x1
Decimation (subsampling) horizontal	increased frame rate
Decimation (subsampling) vertical	increased frame rate
Decimation (subsampling) method	M/C automatic
Decimation (subsampling) factor	2x2



### Model

Frame rate freerun mode	100 fps
Frame rate trigger (continuous)	100 fps
Frame rate trigger (maximum)	112 fps
Exposure time (minimum - maximum)	0.0079 ms - 2000 ms
Long exposure (maximum)	120000 ms
Power consumption	9.2 W - 15.4 W
Image memory	2032 MB

### Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.


Allowed device temperature during operation	0 °C - 55 °C / 32 °F - 131 °F
Allowed device temperature during storage	-20 °C - 60 °C / -4 °F - 140 °F
Humidity (relative, non-condensing)	20 % - 80 %

### Connectors

Interface connector	GigE RJ45, screwable
I/O connector	12-pin M12 connector (Attend 216A-12MSR)
Power supply	12 V - 24 V or PoE+

### Pin assignment I/O connector

1	Power supply, 12-24 V DC
2	Power supply, ground
3	(Trigger) input 0 with optocoupler - Line0
4	Reference level for all optocoupler outputs
5	Reference level for all optocoupler inputs
6	(Trigger) input 1 with optocoupler - Line1
7	(Flash) output 1 with optocoupler - Line4
8	Fast (flash) output 2 with optocoupler - Line5
9	Power supply for fast (flash) outputs, 3-5 V DC
10	Fast (flash) output 3 with optocoupler - Line6
11	(Trigger) input 2 with optocoupler - Line2
12	(Flash) output 0 with optocoupler - Line3



### Design

Lens Mount	C-Mount
IP code	IP30
Dimensions H/W/L	60.0 mm x 75.0 mm x 94.5 mm
Mass	550 g
Housing material	Aluminum

### Features

List of on-camera image pre-processing features.

All features of the table are available via our IDS peak software for image pre-processing on the host computer (sensor model dependent).

Image Acquisition	Freerun	✓
	Software trigger	✓
	Hardware trigger	✓
	Trigger controlled exposure	✓
	Denoiser	✓
	Long exposure	✓
	Line scan	✓

Subject to technical modifications (2026-01-30)

## GV-79L0WP-C-HQ (1008243)

Flashing	Flashing	✓	
	PWM flashing	✓	
Image Adjustments	Auto exposure	✓	
	Auto gain	✓	
	Auto whitebalance	✓	
	Color correction	✓	
	Gamma	✓	
	LUT	✓	
	Mirror/flip	X/Y	
On-board Image Processing	Pixel formats	Mono8 BayerRG8 BayerRG10 BayerRG10p BayerRG12 BayerRG12p BGR8 RGB8 BGR10p32 RGB10p32	
	Region of interest	✓	
	Decimation (FPGA)	✓	
	Decimation (Sensor)	2x2	
	Binning (FPGA)	✓	
	Binning (Sensor)		
	Others	IP settings	✓
		Bandwidth management	✓
Chunks		✓	
Sequencer		-	
PTP		✓	
Firmware update		✓	
1st supported firmware version		3.6	