

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



QUINT UPS, IQ Technology, EtherCAT®, DIN rail mounting, Screw connection, input: 24 V DC, output: 24 V DC / 40 A, charging current: 5 A

## Product description

The intelligent QUINT UPS for integration into established industrial networks: your systems continue to be supplied with uninterrupted power, even in the event of a mains failure. The battery management system with IQ Technology and a powerful battery charger ensures superior system availability.

## Your advantages

- Easy integration into networks using PROFINET, EtherNet/IP, EtherCAT® and USB interfaces
- Evaluation of state of health (SOH) and state of charge (SOC), thanks to the intelligent battery management system (BMS)
- Automatic recognition of the battery capacities and technologies (VRLA-WTR, LI-ION)
- Monitoring of output current and voltage, as well as manual connection and disconnection of the system
- SFB Technology selectively trips standard miniature circuit breakers. Loads connected in parallel continue working.

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2907081       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Product key                          | CMUI43        |
| GTIN                                 | 4055626171722 |
| Weight per piece (including packing) | 752 g         |
| Weight per piece (excluding packing) | 591 g         |
| Customs tariff number                | 85371091      |
| Country of origin                    | CN            |

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## Technical data

### Notes

|         |                                                                                                             |
|---------|-------------------------------------------------------------------------------------------------------------|
| General | EtherCAT® is a registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. |
|---------|-------------------------------------------------------------------------------------------------------------|

### Input data

|                                                                                           |                                            |
|-------------------------------------------------------------------------------------------|--------------------------------------------|
| Input voltage                                                                             | 24 V DC                                    |
| Input voltage range                                                                       | 18 V DC ... 30 V DC                        |
|                                                                                           | 18 V DC ... 32 V DC                        |
| Electric strength, max.                                                                   | 35 V DC                                    |
| Internal input fuse                                                                       | no                                         |
| Voltage type of supply voltage                                                            | DC                                         |
| Inrush current                                                                            | $\leq 9 \text{ A}$ ( $\leq 4 \text{ ms}$ ) |
| Reverse polarity protection                                                               | yes                                        |
| Fixed backup threshold                                                                    | 22 V DC                                    |
| Dynamic activation threshold                                                              | $> 1 \text{ V} / 100 \text{ ms}$           |
| Switch-on time                                                                            | max. 3 s                                   |
| Switch-on time during battery operation (Bat.-Start)                                      | 8 s                                        |
| Voltage drop, input/output                                                                | 0.5 V DC                                   |
| Current consumption $I_N$ ( $U_N$ , $I_{OUT} = I_N$ , $I_{charge} = 0$ )                  | 40.1 A                                     |
| Current consumption $I_{max}$ ( $U_N$ , $I_{OUT} = I_{Stat.Boost}$ , $I_{charge} = max$ ) | 51.2 A                                     |
| Current consumption $I_{No-Load}$ ( $U_N$ , $I_{OUT} = 0$ , $I_{charge} = 0$ )            | 105 mA                                     |
| Current consumption $I_{charge}$ ( $U_N$ , $I_{OUT} = 0$ , $I_{charge} = max$ )           | 6.1 A                                      |
| Power consumption $P_N$ ( $U_N$ , $I_{OUT} = I_N$ , $I_{charge} = 0$ )                    | 967 W                                      |
| Power consumption $P_{max}$ ( $U_N$ , $I_{OUT} = I_{Stat.Boost}$ , $I_{charge} = max$ )   | 1122 W                                     |
| Power consumption $P_{No-Load}$ ( $U_N$ , $I_{OUT} = 0$ , $I_{charge} = 0$ )              | 2.6 W                                      |
| Power consumption $P_{charge}$ ( $U_N$ , $I_{OUT} = 0$ , $I_{charge} = max$ )             | 148 W                                      |

### Output data

|                                  |                                                                               |
|----------------------------------|-------------------------------------------------------------------------------|
| Efficiency                       | typ. 97 %                                                                     |
| Number of outputs                | 1                                                                             |
| Nominal output current ( $I_N$ ) | 40 A (-25 °C ... 50 °C)                                                       |
| Short-circuit-proof              | yes                                                                           |
| No-load proof                    | yes                                                                           |
| Switch-over time                 | 0 ms                                                                          |
| Power dissipation                | 2.8 W (Mains operation)                                                       |
|                                  | 13 W (Mains operation)                                                        |
|                                  | 3.51 W (Battery operation)                                                    |
|                                  | 16.4 W (Battery operation)                                                    |
| UPS connection in parallel       | yes, with decoupling modules (to increase the buffer time and for redundancy) |

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

|                                              |                                  |
|----------------------------------------------|----------------------------------|
| UPS connection in series                     | no                               |
| Energy storage device connection in parallel | Yes, 5 (observe line protection) |
| Energy storage device connection in series   | no                               |

## Mains operation

|                                                               |                                                   |
|---------------------------------------------------------------|---------------------------------------------------|
| Output voltage                                                | 24 V DC ( $U_{OUT} = U_{IN} - 0.5 \text{ V DC}$ ) |
| Output voltage range                                          | 18 V DC ... 30 V DC<br>18 V DC ... 32 V DC        |
| Output current $I_N$                                          | 40 A                                              |
| Static Boost ( $I_{Stat.Boost}$ )                             | 45 A                                              |
| Dynamic Boost ( $I_{Dyn.Boost}$ )                             | 60 A (5 s)                                        |
| Selective Fuse Breaking ( $I_{SFB}$ )                         | 215 A (15 ms)                                     |
| Output power $P_{OUT}$ ( $U_N$ , $I_{OUT} = I_N$ )            | 960 W                                             |
| Output power $P_{OUT}$ ( $U_N$ , $I_{OUT} = I_{stat.Boost}$ ) | 1080 W                                            |

## Battery operation

|                                                               |                                                    |
|---------------------------------------------------------------|----------------------------------------------------|
| Output voltage                                                | 24 V DC ( $U_{OUT} = U_{BAT} - 0.5 \text{ V DC}$ ) |
| Output voltage range                                          | 19 V DC ... 32 V DC                                |
| Output current $I_N$                                          | 40 A                                               |
| Static Boost ( $I_{Stat.Boost}$ )                             | 45 A                                               |
| Selective Fuse Breaking ( $I_{SFB}$ )                         | 215 A (15 ms)                                      |
| Output power $P_{OUT}$ ( $U_N$ , $I_{OUT} = I_N$ )            | 960 W                                              |
| Output power $P_{OUT}$ ( $U_N$ , $I_{OUT} = I_{stat.Boost}$ ) | 1080 W                                             |

## Energy storage

|                                                 |                        |
|-------------------------------------------------|------------------------|
| End-of-charge voltage                           | 32 V DC                |
| End-of-charge voltage (temperature-compensated) | 25 V DC ... 32 V DC    |
| Charging current (configurable)                 | 5 A                    |
| Nominal capacity (without additional charger)   | 7 Ah ... 100 Ah        |
| Max. capacity                                   | 135 Ah                 |
| Charging time                                   | 202.5 h                |
| Buffer time                                     | 45 min (38 Ah)         |
| Deep discharge protection                       | 19.2 V DC              |
| Battery technology                              | VRLA, VRLA-WTR, LI-ION |
| Charge characteristic curve                     | $IU_0U$                |
| IQ-Technology                                   | yes                    |
| Temperature sensor                              | yes                    |
| Temperature compensation (configurable)         | 42 mV/K                |

## Connection data

### Input

|          |     |
|----------|-----|
| Position | 1.x |
|----------|-----|

### Conductor connection

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

|                                              |                        |
|----------------------------------------------|------------------------|
| Connection method                            | Screw connection       |
| rigid                                        | 0.5 mm² ... 16 mm²     |
| flexible                                     | 0.5 mm² ... 16 mm²     |
| flexible with ferrule without plastic sleeve | 0.5 mm² ... 16 mm²     |
| flexible with ferrule with plastic sleeve    | 0.5 mm² ... 16 mm²     |
| rigid (AWG)                                  | 8 ... 6 (Cu)           |
| Stripping length                             | 10 mm (rigid/flexible) |
| Tightening torque                            | 1.2 Nm ... 1.5 Nm      |
| Drive form screw head                        | Slotted L              |

## Output

|          |     |
|----------|-----|
| Position | 2.x |
|----------|-----|

## Conductor connection

|                                              |                        |
|----------------------------------------------|------------------------|
| Connection method                            | Screw connection       |
| rigid                                        | 0.5 mm² ... 16 mm²     |
| flexible                                     | 0.5 mm² ... 16 mm²     |
| flexible with ferrule without plastic sleeve | 0.5 mm² ... 16 mm²     |
| flexible with ferrule with plastic sleeve    | 0.5 mm² ... 16 mm²     |
| rigid (AWG)                                  | 8 ... 6 (Cu)           |
| Stripping length                             | 10 mm (rigid/flexible) |
|                                              | 8 mm (Ferrule)         |
| Tightening torque                            | 1.2 Nm ... 1.5 Nm      |
| Drive form screw head                        | Slotted L              |

## Signal

|          |     |
|----------|-----|
| Position | 3.x |
|----------|-----|

## Conductor connection

|                                              |                       |
|----------------------------------------------|-----------------------|
| Connection method                            | Push-in connection    |
| rigid                                        | 0.2 mm² ... 1 mm²     |
| flexible                                     | 0.2 mm² ... 1 mm²     |
| flexible with ferrule without plastic sleeve | 0.2 mm² ... 0.75 mm²  |
|                                              | 0.5 mm² (recommended) |
| flexible with ferrule with plastic sleeve    | 0.2 mm² ... 0.75 mm²  |
| rigid (AWG)                                  | 24 ... 16 (Cu)        |
| Stripping length                             | 8 mm (rigid/flexible) |

## Battery

|          |     |
|----------|-----|
| Position | 4.x |
|----------|-----|

## Connection technology

|                  |                                                                                                                                                                                                      |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Position marking | 4.1 (+), 4.2 (-), 4.3 (⏏   |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Conductor connection

|                   |                  |
|-------------------|------------------|
| Connection method | Screw connection |
|-------------------|------------------|

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

|                                              |                                            |
|----------------------------------------------|--------------------------------------------|
| rigid                                        | 0.5 mm <sup>2</sup> ... 16 mm <sup>2</sup> |
| flexible                                     | 0.5 mm <sup>2</sup> ... 16 mm <sup>2</sup> |
| flexible with ferrule without plastic sleeve | 0.5 mm <sup>2</sup> ... 16 mm <sup>2</sup> |
| flexible with ferrule with plastic sleeve    | 0.5 mm <sup>2</sup> ... 16 mm <sup>2</sup> |
| rigid (AWG)                                  | 20 ... 6 (Cu)                              |
| Stripping length                             | 10 mm (rigid/flexible)                     |
| Tightening torque                            | 1.2 Nm ... 1.5 Nm                          |
| Drive form screw head                        | Slotted L                                  |

## Interfaces

|                      |                       |
|----------------------|-----------------------|
| Interface            | EtherCAT®             |
| Number of interfaces | 2                     |
| Connection method    | RJ45                  |
| Supported protocols  | CoE                   |
| Locking              | Locking clip          |
| Transmission physics | Twisted-Pair          |
| Features             | Autonegotiation       |
|                      | Autocrossing          |
|                      | Half- or full-duplex  |
|                      | automatic recognition |
| Topology             | Ring                  |
|                      | Line                  |
| Transmission speed   | 100 Mbps              |
| Transmission length  | max. 100 m            |
| Cycle time           | < 100 µs              |
| Access time          | ≤ 2 s                 |
| Chipset              | Renesas R-IN32M3      |
| Electrical isolation | yes                   |
| Device ID            | 2C5B74 <sub>hex</sub> |
| Vendor ID            | 84 <sub>hex</sub>     |

## Signaling

### LED signaling

|                    |                    |
|--------------------|--------------------|
| Types of signaling | DC OK (green)      |
|                    | Alarm (red)        |
|                    | Bat.-Mode (yellow) |
|                    | SOC (red, green)   |
|                    | Data (red, green)  |

## Product properties

|                |           |
|----------------|-----------|
| Product type   | DC UPS    |
| Product family | QUINT UPS |

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

|                                    |                           |
|------------------------------------|---------------------------|
| MTBF (IEC 61709, SN 29500)         | > 1151000 h (25 °C)       |
|                                    | > 718500 h (40 °C)        |
|                                    | > 365200 h (60 °C)        |
| Environmental protection directive | RoHS Directive 2011/65/EU |
|                                    | WEEE                      |
|                                    | Reach                     |

## Insulation characteristics

|                     |                  |
|---------------------|------------------|
| Protection class    | III (without PE) |
| Degree of pollution | 2                |

## Life expectancy (electrolytic capacitors)

|      |          |
|------|----------|
| Time | 126720 h |
|------|----------|

## Dimensions

### Item dimensions

|                                          |                                           |
|------------------------------------------|-------------------------------------------|
| Width                                    | 47 mm                                     |
| Height                                   | 130 mm                                    |
| Depth                                    | 125 mm                                    |
| Depth (Device depth (DIN rail mounting)) | 125 mm (Device depth (DIN rail mounting)) |

### Item dimensions with alternative mounting

|        |        |
|--------|--------|
| Width  | 123 mm |
| Height | 130 mm |
| Depth  | 49 mm  |

### Installation dimensions

|                                                    |                                       |
|----------------------------------------------------|---------------------------------------|
| Installation distance right/left (active)          | 5 mm / 5 mm ( $P_{Out} \geq 50\%$ )   |
| Installation distance right/left (passive)         | 0 mm / 0 mm ( $P_{Out} \geq 50\%$ )   |
| Installation distance right/left (active, passive) | 0 mm / 0 mm ( $P_{Out} \leq 50\%$ )   |
| Installation distance top/bottom (active)          | 50 mm / 50 mm ( $P_{Out} \geq 50\%$ ) |
| Installation distance top/bottom (passive)         | 40 mm / 20 mm ( $P_{Out} \geq 50\%$ ) |
| Installation distance top/bottom (active, passive) | 40 mm / 20 mm ( $P_{Out} \leq 50\%$ ) |

## Mounting

|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| Mounting type     | DIN rail mounting                                              |
| Mounting position | On horizontal DIN rail NS 35/7.5 and NS 35/15 acc. to EN 60715 |

## Material specifications

|                                                                    |                        |
|--------------------------------------------------------------------|------------------------|
| Flammability rating according to UL 94 (housing / terminal blocks) | V0                     |
| Housing material                                                   | Metal                  |
| Hood version                                                       | Stainless steel X6Cr17 |
| Side element version                                               | Aluminum AlMg3         |

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## Environmental and real-life conditions

### Ambient conditions

|                                                |                                                                   |
|------------------------------------------------|-------------------------------------------------------------------|
| Degree of protection                           | IP20                                                              |
| Ambient temperature (operation)                | -25 °C ... 70 °C (> 60 °C Derating: 2,5 %/K)                      |
| Ambient temperature (storage/transport)        | -40 °C ... 85 °C                                                  |
| Ambient temperature (start-up type tested)     | -40 °C                                                            |
| Maximum altitude                               | ≤ 4000 m                                                          |
| Climatic class                                 | 3K3 (EN 60721)                                                    |
| Max. permissible relative humidity (operation) | ≤ 95 % (at 25 °C, non-condensing)                                 |
| Shock                                          | 18 ms, 30g, in each space direction (according to IEC 60068-2-27) |
| Vibration (operation)                          | 2.3g                                                              |

## Standards and regulations

### Protective extra-low voltage

|                          |                              |
|--------------------------|------------------------------|
| Standard designation     | Protective extra-low voltage |
| Standards/specifications | IEC 61010-1 (SELV)           |
|                          | IEC 61010-2-201 (PELV)       |

## Approvals

### UL approval

|                |                           |
|----------------|---------------------------|
| Identification | UL/C-UL Listed UL 61010-1 |
|----------------|---------------------------|

### UL approval

|                |                               |
|----------------|-------------------------------|
| Identification | UL/C-UL Listed UL 61010-2-201 |
|----------------|-------------------------------|

### UL approval

|                |                                                                                                 |
|----------------|-------------------------------------------------------------------------------------------------|
| Identification | UL/C-UL Listed ANSI/ISA-12.12.01 Class I, Division 2, Groups A, B, C, D T4 (Hazardous Location) |
|----------------|-------------------------------------------------------------------------------------------------|

### CSA

|                |                              |
|----------------|------------------------------|
| Identification | CAN/CSA-C22.2 No. 61010-1-12 |
|----------------|------------------------------|

### CSA

|                |                         |
|----------------|-------------------------|
| Identification | CAN/CSA-IEC 61010-2-201 |
|----------------|-------------------------|

### CSA

|                |                                                                                      |
|----------------|--------------------------------------------------------------------------------------|
| Identification | CAN/CSA-C22.2 No. 213 Class I, Division 2, Groups A, B, C, D T4 (Hazardous Location) |
|----------------|--------------------------------------------------------------------------------------|

### CB scheme

|                |                 |
|----------------|-----------------|
| Identification | IEC 61010-1     |
|                | IEC 61010-2-201 |

### DNV

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

|                |                                                                                                |
|----------------|------------------------------------------------------------------------------------------------|
| Identification | Class Guideline DNVGL-CG-0339                                                                  |
| Note           | Location classes: Temperature D (see Application/Limitation), Humidity B, Vibration A/C, EMC B |

## EMC data

|                                     |                                                                                                                                                        |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electromagnetic compatibility       | Conformance with EMC Directive 2014/30/EU                                                                                                              |
| Low Voltage Directive               | Conformance with Low Voltage Directive 2014/35/EC                                                                                                      |
| EMC requirements for noise emission | EN 61000-6-3<br>EN 61000-6-4                                                                                                                           |
| EMC requirements for noise immunity | EN 61000-6-1<br>EN 61000-6-2                                                                                                                           |
| Noise immunity                      | Immunity in accordance with EN 61000-6-1 (residential), EN 61000-6-2 (industrial), and EN 61000-6-5 (switching devices), IEC/EN 61850-3 (power supply) |

## Noise emission

|                       |                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------------------------|
| Standards/regulations | Additional basic standard EN 61000-6-5 (immunity in switching devices), IEC/EN 61850-3 (power supply) |
|-----------------------|-------------------------------------------------------------------------------------------------------|

## Electrostatic discharge

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-2 |
|-----------------------|--------------|

## Electrostatic discharge

|                   |                      |
|-------------------|----------------------|
| Contact discharge | 8 kV (Test Level 4)  |
| Discharge in air  | 15 kV (Test Level 4) |
| Comments          | Criterion B          |

## Electromagnetic HF field

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-3 |
|-----------------------|--------------|

## Electromagnetic HF field

|                     |                       |
|---------------------|-----------------------|
| Frequency range     | 80 MHz ... 1 GHz      |
| Test field strength | 20 V/m (Test Level 3) |
| Frequency range     | 1 GHz ... 6 GHz       |
| Test field strength | 10 V/m (Test Level 3) |
| Frequency range     | 1 GHz ... 6 GHz       |
| Test field strength | 10 V/m (Test Level 3) |
| Comments            | Criterion A           |

## Fast transients (burst)

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-4 |
|-----------------------|--------------|

## Fast transients (burst)

|          |                                    |
|----------|------------------------------------|
| Input    | 4 kV (Test Level 4 - asymmetrical) |
| Output   | 4 kV (Test Level 4 - asymmetrical) |
| Signal   | 4 kV (Test Level 4 - asymmetrical) |
| Comments | Criterion B                        |

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## Surge voltage load (surge)

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-5 |
|-----------------------|--------------|

## Surge voltage load (surge)

|          |                                    |
|----------|------------------------------------|
| Input    | 1 kV (Test Level 3 - symmetrical)  |
|          | 2 kV (Test Level 3 - asymmetrical) |
| Output   | 1 kV (Test Level 3 - symmetrical)  |
|          | 2 kV (Test Level 3 - asymmetrical) |
| Signal   | 1 kV (Test Level 2 - asymmetrical) |
| Comments | Criterion B                        |

## Conducted interference

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-6 |
|-----------------------|--------------|

## Conducted interference

|                     |                     |
|---------------------|---------------------|
| Input/output/signal | asymmetrical        |
| Frequency range     | 0.15 MHz ... 80 MHz |
| Comments            | Criterion A         |
| Voltage             | 10 V (Test Level 3) |


## Power frequency magnetic field

|                       |                 |
|-----------------------|-----------------|
| Standards/regulations | EN 61000-4-8    |
| Frequency             | 16.67 Hz        |
|                       | 50 Hz           |
|                       | 60 Hz           |
| Test field strength   | 100 A/m         |
| Additional text       | 60 s            |
| Comments              | Criterion A     |
| Frequency             | 50 Hz           |
|                       | 60 Hz           |
| Frequency range       | 50 Hz ... 60 Hz |
| Test field strength   | 1 kA/m          |
| Additional text       | 3 s             |
| Frequency             | 0 Hz            |
| Test field strength   | 300 A/m         |
| Additional text       | DC, 60 s        |


## Criteria

|             |                                                                                      |
|-------------|--------------------------------------------------------------------------------------|
| Criterion A | Normal operating behavior within the specified limits.                               |
| Criterion B | Temporary impairment to operational behavior that is corrected by the device itself. |

Drawings



Block diagram




QUINT DC UPS buffer times for PB battery module

QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081  
<https://www.phoenixcontact.com/pc/products/2907081>

Graphic



The data is based on an ambient temperature of +25 °C at the start of use.

1460921 UPS-BAT/LI/24DC/64WH


1460922 UPS-BAT/LI/24DC/189WH

1396415 UPS-BAT/LI/24DC/128WH

1460923 UPS-BAT/LI/24DC/284WH

QUINT DC UPS buffer times for LI battery module

Graphic



The data is based on an ambient temperature of +25 °C at the start of use.

2320416 UPS-BAT/VRLA-WTR/24DC/13AH

2320429 UPS-BAT/VRLA-WTR/24DC/26AH

QUINT DC UPS buffer times and VRLA-WTR battery module

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2907081>



**EAC**

Approval ID: RU S-DE.BL08.W.00764



**UL Listed**

Approval ID: E123528



**cUL Listed**

Approval ID: E123528



**EAC**

Approval ID: RU-DE.B.00184/20

**DNV**

Approval ID: TAA00002K4



**KC**

Approval ID: R-R-PCK-2907081



**LR**

Approval ID: LR21417906TA



**NK**

Approval ID: TA22372M



**BV**

Approval ID: 69394/A0 BV



**RINA**

Approval ID: ELE382621XG

**ABS**

Approval ID: 23-2416092-PDA

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>



**cUL Listed**

Approval ID: E199827



**UL Listed**

Approval ID: E199827

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081  
<https://www.phoenixcontact.com/pc/products/2907081>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27040705 |
| ECLASS-15.0 | 27040705 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000382 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121000 |
|-------------|----------|

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081  
<https://www.phoenixcontact.com/pc/products/2907081>

## Environmental product compliance

|                                         |                                                                                                                                                                                                                                   |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS                                 |                                                                                                                                                                                                                                   |
| Fulfills EU RoHS substance requirements | Yes                                                                                                                                                                                                                               |
| Exemption                               | 7(a), 7(c)-I                                                                                                                                                                                                                      |
| China RoHS                              |                                                                                                                                                                                                                                   |
| Environment friendly use period (EFUP)  | EFUP-25                                                                                                                                                                                                                           |
|                                         | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC                           |                                                                                                                                                                                                                                   |
| REACH candidate substance (CAS No.)     | Diboron trioxide(CAS: 1303-86-2)                                                                                                                                                                                                  |
|                                         | Lead(CAS: 7439-92-1)                                                                                                                                                                                                              |
| SCIP                                    | 223d7b52-83fe-40a8-bfdc-486b6e6b6e41                                                                                                                                                                                              |
| EF3.0 Climate Change                    |                                                                                                                                                                                                                                   |
| CO2e kg                                 | 32.85 kg CO2e                                                                                                                                                                                                                     |

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## Mandatory accessories

### UPS-BAT/PB/24DC/7AH - Battery module

1274118

<https://www.phoenixcontact.com/pc/products/1274118>



Battery module (device with battery), VRLA-AGM, 24 V DC, 7 Ah, automatic detection and communication with QUINT UPS-IQ

---

### UPS-BAT/PB/24DC/12AH - Battery module

1274119

<https://www.phoenixcontact.com/pc/products/1274119>



Battery module (device with battery), VRLA-AGM, 24 V DC, 12 Ah, automatic detection and communication with QUINT UPS-IQ

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## UPS-BAT/PB/24DC/20AH - Battery module

1348516

<https://www.phoenixcontact.com/pc/products/1348516>



Battery module (device with battery), VRLA-AGM, 24 V DC, 20 Ah, automatic detection and communication with QUINT UPS-IQ

---

## UPS-BAT/PB/24DC/40AH - Battery module

1354641

<https://www.phoenixcontact.com/pc/products/1354641>



Battery module (device with battery), VRLA-AGM, 24 V DC, 40 Ah, automatic detection and communication with QUINT UPS-IQ

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## UPS-BAT/LI/24DC/128WH - Battery module

1396415

<https://www.phoenixcontact.com/pc/products/1396415>



Battery module (device with battery), Lithium-Ion (LiFePO<sub>4</sub>), 24 V DC, 128 Wh. For use with a QUINT UPS for ambient temperatures (charging) of 0°C ... 60°C and a maximum charging current of 5 A. For charging below 0°C, please note the permissible UPS V/C level.

---

## UPS-BAT/VRLA-WTR/24DC/13AH - Battery module

2320416

<https://www.phoenixcontact.com/pc/products/2320416>



Battery module (device with battery), lead AGM, VRLA technology 24 V DC, 13 Ah, tool-free battery change, automatic detection, and communication with QUINT UPS-IQ

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## UPS-BAT/VRLA-WTR/24DC/26AH - Battery module

2320429

<https://www.phoenixcontact.com/pc/products/2320429>



Battery module (device with battery), lead AGM, VRLA technology 24 V DC, 26 Ah, tool-free battery change, automatic detection, and communication with QUINT UPS-IQ

---

## UPS-BAT/LI/24DC/189WH - Battery module

1460922

<https://www.phoenixcontact.com/pc/products/1460922>



Battery module (device with battery), Lithium-Ion (LiFePO<sub>4</sub>), 24 V DC, 189 Wh

# QUINT4-UPS/24DC/24DC/40/EC - Uninterruptible power supply



2907081

<https://www.phoenixcontact.com/pc/products/2907081>

## UPS-BAT/LI/24DC/284WH - Battery module

1460923

<https://www.phoenixcontact.com/pc/products/1460923>



Battery module (device with battery), Lithium-Ion (LiFePO<sub>4</sub>), 24 V DC, 284 Wh

---

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)